

# WASTOP® INLINE CHECK VALVE

## WaStop 390

<b>Model Name</b>	WS390
<b>Nominal Diameter</b>	DN 400
<b>Fasteners mtrl.</b>	EN 1.4404
<b>Gasket Mtrl.</b>	EPDM
<b>Weight [kg]</b>	20.3
<b>Min. ID Host Pipe [mm]</b>	393
<b>Max. ID Host Pipe [mm]</b>	411
<b>Max. Flow Vel. [m/s]</b>	3
<b>Max. Flow Vol. [l/s]</b>	378

## Product Variants

Art. No	WS390-S3-316	WS390-S4-316
<b>Membrane mtrl.</b>	Polyurethane	Polyurethane
<b>Valve Body mtrl.</b>	EN 1.4404	EN 1.4404
<b>Max. Back Pressure [mmH<sub>2</sub>O]</b>	5	8
<b>Horizontal Opening [mmH<sub>2</sub>O]</b>	385	410
<b>Horizontal Closing [mmH<sub>2</sub>O]</b>	195	270
<b>Submerged Opening [mmH<sub>2</sub>O]</b>	210	250
<b>Submerged Closing [mmH<sub>2</sub>O]</b>	55	65
<b>Vertical Opening [mmH<sub>2</sub>O]</b>	420	450
<b>Vertical Closing [mmH<sub>2</sub>O]</b>	290	330

